SYMPLYPRO XTL TAPE LIBRARIES

PRO XTL 8

Compact 1RU entry-level library for reliable data protection

Overview

The SymplyPRO XTL 8 library is built on field-proven technology, trusted by some of the world's largest organizations. Designed for seamless integration, this library offers a wide range of connectivity options, including native SAS and Fibre Channel, with Ethernet (iSCSI), and Thunderbolt connectivity enabled via external bridge devices, ensuring both compatibility and optimum connectivity within your existing infrastructure and alongside your chosen data protection, backup, and archive applications.

SymplyPRO XTL 8 is a compact 1RU entry-level library is designed for reliable data protection, featuring support for current LTO generations, including LTO-7, LTO-8 and LTO-9 half-height tape drives. The XTL 8 is idea for SMBs, providing an impressive balance between capacity and total cost of ownership.

Managing your SymplyPRO XTL 8 library is simple, with front panel controls that are paired with the LCD display, while secure web-based management provides effortless control while also enabling you to monitor the status of your library, update firmware, perform diagnostics, and access industry-leading technical support – all from anywhere in the world.

KEY FEATURES & BENEFITS

All PRO XTL Models

- Effortless Installation and User-Friendly Interface
- Fast Performance and Uncompromising Reliability
- Modular Design for Servicing
- No Restrictive Capacity or Partition Licenses
- Versatile Connectivity Options: SAS, Fibre Channel
- Industry-leading 3-Year Warranty and Technical Support

PRO XTL 8 Specifications

- Compact 1RU Entry-level Library for Reliable Data Protection
- 8 LTO Cartridge Slots, 1 Half-Height LTO Drive
- SAS or Fibre Channel Connectivity
- Uncompressed Capacity up to 144TB (LTO-9)
- 3-year Warranty and Industry-leading Support

Highlights

- Supports up to 8 LTO Cartridges Concurrently
- 1 Half-Height Tape Drive
- LTO-7, LTO-8 or LTO-9 with SAS or FC interface
- Front Operator Panel with LCD
- Modular Drive

- Two Removable Magazines for Bulk Load/Unload
- Remote Management and Monitoring via Ethernet
- Encryption capable
- Drive and Library Firmware Update via Remote Management, or via Front Operator Panel and Connected USB Storage

SYMPLY**PRO XTL** TAPE LIBRARIES

PRO XTL 8

Compact 1RU entry-level library for reliable data protection

Technical Specifications	PRO XTL 8
Rack Units	1RU
Number of Tape Slots	8
Number of Tape Drives	1 Half-Height
Native Drive Interface	SAS or Fibre Channel
Integrated Host Interface (optional)	10Gb Ethernet (iSCSI) or Thunderbolt via 1RU External Bridge
Number of Magazines	2
Mail Slots (Import/Export)	1
Optional Scalability	Not available (XTL 40 and XTL 80 only)
Robotic MSBF	1,000,000
Barcode Reader	Yes
Rack Kit	Yes
Physical Dimensions (DxWxH)	740 x 447 x 44.5mm / 29.1 x 17.6 x 3.50"
Weight (without tape drives)	11.3kg / 25lbs

Power and Environmental Conditions	PRO XTL 8
Power Connection	100 - 240 VAC/80W
Humidity	20—50% Non-condensing (operating) 5—80% Non-condensing (transport) Max operating humidity change per hour = 5%
Temperature	10—35°C / 50—86°F (operating) -30—60°C / -22—140°F (transport) Max operating temperature change per hour = 5°C / 41°F
Altitude	3,048m / 10,000' (operating) 12,192m / 40,000' (transport)